PRE-FILLED IP68

JOINTING BOXES





Electrical performance:

- CEI EN 50393 as applicable
- Class 2 in accordance with CEI 64-8.



Norking temperature: 90°

Installation temperature: -40°C / +50°C

₩ Fully submersible

Can be used underground

Halogen-free Gel

UV resistant

Self-extinguishing and resistant to abnormal heat and fire:

Glow Wire Flammability Index at +960° C according to EN60695-2-12

IP68 OFFICIALLY TESTED

IMC



BOB


The IP68 / IP69K micro-joints, gel pre-filled, complete with connector, suitable for any type of installation, even the most extreme.


Extremely compact and space-saving, pre-filled with soft, highly conformable gel. With minimal aesthetic impact and visually pleasing. Equipped with integrated cable glands for IP68 and IP69K degree of ingress protection and cable retention.

ADVANTAGES

- ▶ Pre-filled with a gel that is not-classified as hazardous under the CLP Directive.
- Extremely compact and ready to install.
- ► Ideal for connections in lighting systems for gardens, steps and stairways, pedestrian crossings, etc.
- ▶ Pre-threaded entries for the positioning of the clamping nuts.
- No shelf life.


► Always re-enterable.





JOINTING BOXES


Some installation possibilities for BOB 4








For use in traps. The ideal accessory for branch connections from a through cable to light fittings and spotlights. Suitable in applications where there is presence of water and moisture.





PRODUCT / Item	Colour		e formation mm²) Branch	Cables Ø min - max (mm)	Pieces Pack	(mm)
BOB 3 BOB3	•	1 cable 3 x 4 3 x 2,5	2 cables 3 x 4	8 - 13	1 piece Blister	105 x 80 x 25
BOB 3 - N BOB3-N	•		2 cables 3 x 2,5		1 piece Blister	

PRODUCT / Item	Colour		e formation mm²) Branch	Cables Ø min - max (mm)	Pieces Pack	(mm)
BOB 4 BOB	•	1 cables 3 x 4 3 x 2,5	2 cables 3 x 4	8 - 13	1 piece Blister	105 x 65 x 25
BOB 4 - N BOB4-N	•		3 cables 3 x 2,5		1 piece Blister	

